




Tehničke informacije								Premium			Clever			
Napon [V]	Kapacitet [Ah]	Wh	Dužina [mm]	Širina [mm]	Visina [mm]	Težina [Kg]	Terminal	TAB Code	Code	Cena [RSD]	TAB Code	Code	Opcija	Cena [RSD]
6,4	4,5	28,8	90	70	101	0,6	F1	8436555	HD6-4-4-5P	3,725				
12,8	4,5	57,6	90	70	101	0,75	F1	8415448	HD12-4-5P	6,730				
12,8	12	153,6	152	99	96	1,7	F2	8442805	HD12-12P	16,465	8444972	HD12-12C		11,410
12,8	20	256	181	77	167	3	M5	8436576	HD12-20P	27,680	8443825	HD12-20C		19,840
12,8	45	576	197	165	170	7,52	M6	8443000	HD12-45P	53,072				
12,8	50	640	228	132	215	6,8	M6	8443358	HD12-50P-BLE	62,000	8443360	HD12-50C-BLE	BT	44,520
12,8	50	640	228	132	215	6,8	M6	8443357	HD12-50P-SOC	58,530	8443359	HD12-50C-SOC	SoC	41,170
12,8	65	832	260	168	208	9,3	M6	8443364	HD12-65P-BLE	75,640	8443367	HD12-65C-BLE	BT	54,800
12,8	65	832	260	168	208	9,3	M6	8443363	HD12-65P-SOC	72,170	8443365	HD12-65C-SOC	SoC	51,460
12,8	75	960	260	168	208	10,8	M6	8443648	HD12-75P-SOC	81,470	8444978	HD12-75C-BLE	BT	61,130
12,8	80	1024	259	168	208	10,8	M6	8443369	HD12-80P-BLE	94,120	8443371	HD12-80C-BLE	BT	66,960
12,8	80	1024	259	168	208	10,8	M6	8443368	HD12-80P-SOC	90,890	8443370	HD12-80C-SOC	SoC	63,740
12,8	100	1280	330	173	212	13,6	M8	8443373	HD12-100P-BLE	117,305	8443375	HD12-100C-BLE	BT	83,200
12,8	100	1280	330	173	212	13,6	M8	8443372	HD12-100P-SOC	114,080	8443374	HD12-100C-SOC	SoC	79,980
12,8	100	1280	335	175	190	11,2	M8	8443298	HD12-100P-BLE-R	117,305			BT	
12,8	100	1280	335	175	190	12	M8	8443377	HD12-100P-BLE-L	117,305	8443379	HD12-100C-BLE-L	BT	83,200
12,8	100	1280	355	170	188	13,2	M8	8443376	HD12-100P-SOC-L	114,080	8443378	HD12-100C-SOC-L	SoC	79,980
12,8	120	1536	410	177	225	13,6	M8	8443380	HD12-120P-SOC	132,930	8443383	HD12-120C-BLE	BT	95,600
12,8	120	1536	410	177	225	13,6	M8	8443381	HD12-120P-BLE	136,150	8443382	HD12-120C-SOC	SoC	92,130
12,8	144	1843	330	173	212	15,2	M8	8445147	HD-12-144P-BLE	136,030			BT	
12,8	144	1843	330	173	212	15,2	M8	8442120	HD-12-144P	132,680				
12,8	150	1920	483	170	238	16,5	M8	8443384	HD12-150P-SOC	166,160	8443386	HD12-150C-SOC	SoC	117,430
12,8	150	1920	483	170	238	16,5	M8	8443385	HD12-150P-BLE	169,630	8443387	HD12-150C-BLE	BT	120,900
12,8	200	2560	522	240	220	27	M8	8443388	HD12-200P-SOC	221,590	8443390	HD12-200C-SOC	SoC	155,120
12,8	200	2560	522	240	220	27	M8	8443389	HD12-200P-BLE	225,060	8443391	HD12-200C-BLE	BT	158,970
12,8	250	3200	522	240	220	31,5	M8	8443392	HD12-250P-SOC	277,140	8443394	HD12-250C-SOC	SoC	197,160
12,8	250	3200	522	240	220	31,5	M8	8443393	HD12-250P-BLE	280,490	8443395	HD12-250C-BLE	BT	200,630
12,8	300	3840	522	268	220	32,5	M8	8443396	HD12-300P-SOC	332,230	8443398	HD12-300C-SOC	SoC	236,350
12,8	300	3840	522	268	220	32,5	M8	8443397	HD12-300P-BLE	335,544	8443399	HD12-300C-BLE	BT	239,820
12,8	375	4800	375	330	266	43	M8	8482963	HD12-375P-BLE	408,330			BT	
25,6	10	256	181	77	167	2,8	M5	8443164	HD24-10P	28,400				
25,6	20	512	195	130	180	3,6	M6	8482964	HD24-20P	46,870				
25,6	50	1280	330	173	212	13,6	M8	8443404	HD24-50P-SOC	117,430	8443406	HD24-50C-SOC	SoC	83,580
25,6	50	1280	330	173	212	13,6	M8	8443405	HD24-50P-BLE	120,780	8443407	HD24-50C-BLE	BT	87,050
25,6	75	1920	483	170	238	16,5	M8	8443414	HD24-75P-SOC	167,650	8443416	HD24-75C-SOC	SoC	117,430
25,6	75	1920	483	170	238	16,5	M8	8443415	HD24-75P-BLE	171,120	8443417	HD24-75C-BLE	BT	120,900
25,6	100	2560	522	240	220	27,6	M8	8443400	HD24-100P-SOC	221,590	8443402	HD24-100C-SOC	SoC	157,110
25,6	100	2560	522	240	220	27,6	M8	8443401	HD24-100P-BLE	231,010	8443403	HD24-100C-BLE	BT	161,080
25,6	125	3200	522	240	220	29,6	M8	8482966	HD24-125P-BLE	335,170			BT	
25,6	150	3840	522	268	224	29,6	M8	8443410	HD24-150P-SOC	331,820	8443412	HD24-150C-SOC	SoC	236,350
25,6	150	3840	522	268	224	29,6	M8	8443411	HD24-150P-BLE	335,170	8443413	HD24-150C-BLE	BT	239,570
51,2	100	5120	500	334	232	50	M8	8482967	HD48-100P-BLE	440,200			BT	
51,2	100	5120	500	334	232	50	M8	8482969	HD48-100P-SOC	437,100			SoC	
51,2	200	10240	570	297	317	85	M8	8482967	HD48-200P-BLE	842,085			BT	
51,2	200	10240	570	297	317	85	M8	8482969	HD48-200P-SOC	838,990			SoC	



CLEVER		Garancija 3 godine (projektovani vek trajanja 15 godina)	4.000 ciklusa pri pražnjenju od 1C na 80% DOD
		Garancija 2 godine (projektovani vek trajanja 10 godina)	2.000 ciklusa pri pražnjenju od 1C na 80% DOD



Opcione karakteristike:	
SoC - (State Of Charge) displej	
BLE - (Bluetooth veza)	
Za artikle do 40Ah - SOC i BLE na zahtev	
Za raspoloživost i sve dodatne informacije kontaktirati:	
TAB Baterije d.o.o. 011/377-44-52	kancelarija@tabbaterije.rs

